



TYPE	E25	A32 B40 E32	A40 B50 E40 F50	A50 B63 E50 F63	A63 B80 E63 F80	A80 B100	A100 B125	
	Clamping force Fmax. (KN)	2,8	5,0	6,8	11,0	18,0	28,0	45,0
Max free stroke (mm)	7,0	7,5	8,0	9,0	10,0	11,0	12,5	
E.M. +/- 0,1 (mm)	6,5	8,5	8,5	10,5	10,5	13,0	13,0	
Expulsion stroke (mm)	0,5	0,5	0,5	0,5	0,5	0,5	0,5	
Fspring (KN)	0,95	1,75	2,3	3,2	5,5	9,5	15,0	
Stroke blocking	4,6	5,1	5,6	6,4	7,4	8,3	9,15	
Lock screw	SW 3	SW 3	SW 4	SW 4	SW 5	SW 6	SW 6	
sw <sub>1</sub>	SW 10	SW 12	SW 15	SW 18	SW 22	SW 27	SW 36	
L <sub>1</sub>	5,5	19,5	27	26,5	31,5	31,5	34,5	
D <sub>1</sub> min.	A/E	25	32	40	50	63	80	100
	B/F		40	50	63	80	100	125
D <sub>6</sub>		14	17	21	26	34	42	53
L <sub>7</sub>		40	62,5	78	84	94	98	124